



## MODEL: VBUN-S50-12V

This LED downlight has a dense design with a slim profile of just 4 mm (0.16 inches) depth making it look recessed and seamlessly blends into the surface. This makes it suitable for mounting on any desired location (indoor only). The lightweight aluminum housing can be easily mounted through screws. The downlight uses 5 watts of power, operating on 12V DC. Its modern, sleek design is available in 3 color finish in different color temperatures from amber white, soft white, and warm white tone for soothing light applications to natural white, daylight for offices, and other commercial working spaces. They work with a 12V power supply with low power consumption and high energy efficiency.



PART NUMBER BUILDER / ORDERING GUIDE			
Example part number: <b>VBUN-S50-12V-GOLD-2400K</b>			
<b>MODEL</b>	<b>FIXTURE COLOR</b>	<b>COLOR TEMPERATURE</b>	
VBUN-S50-12V			
	Black	2400K	3500K
	Gold	2700K	4000K
	Brushed Nickel	3000K	5000K

## SPECIFICATIONS

Model No	VBUN-S50-12V
LED Type	12 x 5630 SMD
Rendering Index	CRI>90
Input Voltage	12V DC
Power	5W
Brightness	400-450 Lm
Lifespan	>50,000 hours
Color Temperature	2400K, 2700K, 3000K, 3500K, 4000K, 5000K
Fixture Color	Black, Brushed Nickel and Gold
Fixture Material	Aluminum
Diffuser Material	Polycarbonate Plastic
IP rating	IP20
Dimmable	Yes
Beam angle	120°
Installation Type	Surface Mount
Wire Length	1 meter (39 in)
Operating temperature	-15°C to +40°C
Dimensions	79 mm x 79 mm (3.11 in x 3.11 in)
Depth	4 mm (0.16 in)
Certificates	ETL

